

SE-DU Standard Equipment



www.sumitomoPM.com

Injection Unit

- General purpose screw assembly for unfilled resin
- Fine Flow Control screw assembly
- Profile program for injection: 2 or 5 injection velocity set points, and 2 or 4 hold pressure set points
- Ramping control of injection fill and hold (10 modes)
- Flash Speed Mode for high injection rates
- Three selectable programs for plasticizing
- Injection unit programming in engineering units
- Digital readout of screw position to 0.01mm
- Injection start and plasticizing delay timers
- Peak pressure control during injection
- V/P switchover control (pressure/external signal/position)
- Timers for hold pressure profile to 0.01 sec.
- Screw pull back before and/or after plasticizing
- Screw pull back delay
- Screw pull back delay control
- Auto slowdown function for screw rotation
- Automatic purging program
- Screw cold start-up protection (+/- 5°C from set point)
- Adjustable screw interlock timer with auto-reset
- Nozzle PID temperature control zone
- PID temperature control of barrel zones
- Selectable sprue break with delay timer
- Nozzle contact sensor
- Digital readout of screw RPM
- Water-cooling jacket temperature indicator
- Sliding protective purge shield with interlock
- Injection unit swivel and control panel pivot
- Closed-loop velocity and pressure control system
- Water jacket temperature control zone
- Insulated plasticizing cylinder cover
- SK-II control software
- Synchronized plasticizing

Clamp Unit

- Three-stage mold open/close speed control (%)
- Closed-loop control of mold open/close position and speed
- Selectable auto-ramping modes for clamp open/close
- Low pressure mold protection setting to 0.3mm
- Digital setting of mold open/close positions to 0.1mm
- Digital setting of mold clamping force
- Ejector with selectable multiple functions and speed
- Ejector forward delay and hold timers
- Ejector return confirmation signal
- Manual mode interlock for ejector
- Ejection during mold opening
- Ejection during mold close
- Ejector protrusion during cooling
- Remote setting of ejector stroke (mm), velocity (%) and pressure (%)
- Motorized mold height adjustment
- Standby mode for mold mounting with low clamp speed
- Operator's door interlocked electrically and mechanically
- Operator's door and rear guard with clear PMMA window
- Clamp guard with clear PMMA window
- Emergency stop button on operator & non-operator sides
- Mounting holes on top of fixed platen for robot
- Adjustment-free mechanical safety stop bar
- Grease-lubricated tie bar bushings

Clamp Unit (continued from previous column)

- Central automatic grease lubrication system
- Fully implemented ANSI B151.1-1997 guarding
- Temporary stop of mold open/close
- Mold ejector plate return signal
- Mold valve gate control circuit
- Multi-toggle clamp force control
- Moving platen supports

Electronic & Mechanical Systems

- Full-color, 12.1-inch TFT liquid crystal touch-screen display
- Auto programming of initial molding conditions
- Automatic calendar start-up system
- Multi-language selection
- On-screen operation guide for easy use
- All-in-one setup screen
- Internal memory of 200 mold setup conditions
- Metric or English units selection
- Indicator of current molding cycle phase
- Logging of last 200 setup changes
- Real-time readout of actual operating values
- Graphic display of injection and clamp set values vs. actual
- Running hour meter and shot counter
- Supervision function monitor for unattended operation
- PID barrel temperature control setting to 0.1°C
- Temperature control for production and standby modes
- Fast-rise PID response curve for barrel heat up
- Two-second PID cycle for temperature control
- SSR control circuit for heater bands
- Hi/Lo alarm monitor of barrel temperatures
- Logging and display of abnormal functions
- Product quality control by injection value monitor
- Production control monitor and completion warning
- On-screen operation guide for maintenance
- On-screen diagnostics and troubleshooting
- Printer port (parallel/USB) with print screen function
- Audible warning alarm
- Open machine base with three-way part removal
- Two closed-circuit water connection lines
- Mold open/close signals for hot runner (Spear)
- Spare power supply receptacle
- Robot interface with ejected product sensor
- Heater band burnout monitor and alarm
- Auxiliary facility monitor
- Production and quality monitoring with stocker feed signal
- Auto start of heater bands with output signal
- External mold setup data storage by USB memory
- PC communication circuit port
- Five of 24 output signal selection
- Robot interface circuit (5 in/out relay contacts)

Note:

Specifications subject to change without notice.



1266 Oakbrook Dr., Norcross, GA 30093
PH: (770) 447-5430